



Application of Microramp Flow Control Devices to an Oblique Shock Interaction

Stefanie Hirt

Bernhard Anderson

ABSTRACT

Tests are planned in the 15cm x 15cm supersonic wind tunnel at NASA Glenn to demonstrate the applicability of micro-ramp flow control to the management of shock wave boundary layer interactions. These tests will be used as a database for computational fluid dynamics (CFD) validation and Design of Experiments (DoE) design information. Micro-ramps show potential for mechanically simple and fail-safe boundary layer control.



Application of Microramp Flow Control Devices to an Oblique Shock Interaction


Stefanie Hirt
Bernhard Anderson



Boundary Layer Management



Bleed

- Removes low energy fluid
- Complex System
- Drag penalties



Microramps

- Boundary layer mixing
- Mechanically simple
- Fail-safe





Test Goals and Objectives

Research Goal:

To demonstrate the applicability of micro-ramp flow control for management of shock wave boundary layer (SWBL) interactions.

Research Objectives:

- (1) To develop an experimental data base of CFD validation and Design of Experiments (DOE) design information.**
- (2) To evaluate DOE designs for accuracy and cost effectiveness based on experimental data base.**
- (3) To validate CFD analysis of micro-ramp actuators based on experimental data base.**


Types of Experiments:

- (1) Oblique shock wave boundary layer interactions.**
- (2) Normal shock wave boundary layer interactions.**




15x15cm Microramp Flow Control Tests

Oblique SWBL Experiments




No Flow Control




Micro- Ramp Flow Control

Normal SWBL Experiments



No Flow Control




Micro- Ramp Flow Control



Facility Information



15x15 cm Supersonic Wind Tunnel

- Mach Number: 2.0
- Reynolds Number: $1.5 \times 10^6 - 5 \times 10^6$ /ft
- Inflow: 40 psig pressure at ambient temperature
- Exhaust: ~ 2.0 psia
- Boundary Layer Thickness: ~ 0.5 in (1.3 cm)
- Microramp x-location: -5.12 in (-13.0 cm)





Microramp Parameters






Parameter Values

Spacing, s (mm):	25	30	35
Height, h (mm):	3.0	4.0	5.0
Chord, c (mm):	12	18	24

Central Composite DOE: 15 Cases
Every Combination: 27 Cases



DOE Designs



Main Effects Design - 4 cases

D-Optimal Design - 6 cases

Full Factorial Design - 8 cases

Central Composite Design - 15 cases




Response Variables

Boundary Layer Pitot Pressure Recovery	PTAVE
Boundary Layer Total Pressure Recovery	PFAVE
Compressible Displacement Thickness	δ^*
Compressible Momentum Thickness	θ
Incompressible Shape Factor	H_i






Oblique Shock / Microramp Interaction

CFD Calculation





Reference Plane Profiles





Microramp Optimization



DOE Design	s (mm)	h (mm)	c (mm)	PREF	δ^* (cm)	θ (cm)	Htr
Main Effects (4 points)	25.0	5.0	24.0	0.829	0.427	0.247	1.237
D-Optimal (6 points)	25.0	5.0	24.0	0.801	0.433	0.242	1.237
Full Factorial (8 points)	25.0	5.0	24.0	0.793	0.428	0.239	1.254
Central Composite (15 points)	25.0	5.0	24.0	0.813	0.440	0.239	1.239

- . Optimal design obtained by minimizing Htr
- . Based on CFD results






Experimental Grid Resolution Study

13 x 25 (Test)



51 x 50 (Reference)





Test Schedule

	FY07				FY08				FY09				FY10			
	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
15x15 cm Wind Tunnel																
Test Cell Prep																
Microramps - Oblique																
Isolator Test																
Microramps - Normal																
Buildup Shutdown																
Inlet Wind Tunnel Test																
Microramp Inlet Test																
-Aero Design																
-Design and Fab																
-Testing																



Final Remarks


- CFD for the Oblique Shock Interaction is complete. Experimental testing will begin soon.
- Issues affecting the experimental data were resolved.
 - Data resolution
 - Static pressure gradient
 - Boundary layer edge selection
- Normal Shock Interaction test conditions are being finalized.
- Future Plans:
 - Fail-Safe Hybrid Flow Control
 - Multiple Shock Interaction with Microramps
 - Large Scale Inlet Test with Microramp Flow Control




Backup




Advanced Inlet Flow Control Central Composite Face Centered Design Total Pressure Contours




Config. rvg400




Config. rvg401




Config. rvg402




Config. rvg403




Config. rvg404




Config. rvg405



Config. rvg406




Config. rvg407




Config. rvg408




Advanced Inlet Flow Control Central Composite Face Centered Design Total Pressure Contours




Config. rvg407




Config. rvg408




Config. 409




Config. rvg410




Config. rvg411




Config. rvg412



Config. rvg413



Config. rvg414



Config. rvg415